

## **INSTALLATION INSTRUCTIONS #INST003:**

**REALTRUCK BACKRACK KIT #30102, 30102TB, 30102TB31** 1997-2003 F-150 Safety Rack Only ( No Supercrew )

### **READ THIS NOW!**

Your truck should look like the one shown. If you think you are missing any parts, think that this part number is not for your truck or have any installation question, call our customer service department at toll free:

888-588-6101or locally 800-265-8137.
Other ways to reach RealTruck Backrack:
email: info@backrack.ca
Support@backrack.com



The RealTruck Backrack is secured to your truck with a pair of "Stake Pocket Bolts" specifically designed for your make and model of truck. These bolts mount into each of the two front stake pockets. The RealTruck Backrack assembly sits on the bed rails of your truck and is secured to these Stake Pocket Bolts. If your truck has a BEDLINER we suggest you remove it to install the Stake Pocket Bolts

#### PARTS LIST FOR KIT #30102

PART	DESCRIPTION	QTY	
RMB502P	Rail Mount Bracket Assy Passenger	1	
RMB502D	Rail Mount Bracket Assy Driver	1	
HARDWARE BAG502			
INST003	Installation Instruction	1	
FYZ008	1/2"-20 Nylon Hex Lock Nut	2	
FYZ009	1/2"-13 Hex Nut	4	
FYZ010	1/2" Lock Waser	4	
FYZ011	1/2" Flat Washer	2	
FYZ012	1/2" Flat Washer Large	2	
FYZ014	1/2"-20 x 3.25" Carrige Bolt Grade 8	2	
FYZ023	1/2"-13 UNC THREADED PLATE	2	
SBY502P	Stake Pocket Bolt Passenger	1	
SBY502D	Stake Pocket Bolt Driver	1	

#### PARTS LIST FOR KIT #30102TB, 30102TB31


PART	DESCRIPTION	QTY	
TB502D	Toolbox Bracket Driver	1	
TB502P	Toolbox Bracket Passenger	1	
OR			
TB903D	31" Toolbox Bracket Driver	1	
TB903P	31" Toolbox Bracket Passenger	1	
HARDWARE BAG502			
INST003	Installation Instruction	1	
FYZ008	1/2"-20 Nylon Hex Lock Nut	2	
FYZ009	1/2"-13 Hex Nut	4	
FYZ010	1/2" Lock Waser	4	
FYZ011	1/2" Flat Washer	2	
FYZ012	1/2" Flat Washer Large	2	
FYZ014	1/2"-20 x 3.25" Carrige Bolt Grade 8	2	
FYZ023	1/2"-13 UNC THREADED PLATE	2	
SBY502P	Stake Pocket Bolt Passenger	1	
SBY502D	Stake Pocket Bolt Driver	1	





# REALTRUCK BACKRACK


For each stake pocket bolt (driver and passenger) install the threaded plate. Thread the plate on so there is sufficient thread for the washers and nut. Insert through the slot on the truck bed. Install the 1/2" large steel washer, lock washer and nut. Leave assembly finger tight at this stage.




2

Fasten the RealTruck
Backrack to the Rail
mount bracket, or
Toolbox bracket. Finger
tighten at this stage.

\*\*IMPORTANT\*\*
Install the carriage bolt as shown in the diagram with the round head closest to the cab. Failure to do so could result in damage to the cab or rear window.





KIT #30102

Fasten the RealTruck Backrack Assembly to the Stake pocket bolt as shown.

Center the RealTruck
Backrack assembly on the
truck and final torque all bolts
starting with the nuts on the
inside of the truck bed, then
the rail mount or toolbox
bracket and finally the main
RealTruck Backrack carriage
bolt.

